30-C Harness 2point Harness

Product Datasheet

OUR REF: 30-C

PRODUCT DESCRIPTION

The CLIMAX model 30-C fall arrest harness is especially designed and manufactured to work in situations where there is a risk of falling from a height. Its 2 anchoring points enable the user to be safely secured at the workplace. The harness adapts perfectly to the user's body thanks to its leg strap length adjusters, enabling the user to work in total comfort and with freedom of movements.

Maximum Life of product from manufacture date is 5 years

NOTE: Activities at height are dangerous activities which may lead to severe injury or even death. Gaining an adequate apprenticeship in appropriate techniques and methods of safety is your own responsibility.



Technical Details

These products are classed as Personal Protective Equipment (PPE) under the EU Directive 89/686/EEC **EN 361:2002** "Personal protective equipment against falls from a height - Full body harnesses"

MEETS: EN 361: 2002 Personal protective equipment against falls from a height. Full body harnesses

EC type examination(s) carried out by: Standards: EN 361: 2002 R. D.1407/1992 Certificate No. 3761 Regulatory agency No. 0159

Technical data

Width of main straps 45 mm
Width of secondary straps 20 mm
Resistance of the straps to breakage by traction 40 kN
Static resistance of the harness
Upward traction >15 kN
Downward traction >15 kN
Dynamic behaviour of the harness
Falling head first (Free fall height 4 m) COMPLIANT
Falling feet first (Free fall height 4 m) COMPLIANT

Additional Information:

Inspection

- In addition to the harness being inspected before and after use, a periodic in-depth inspection inspection must be carried out by a competent inspector at least once every 12 months.
- The frequency of of the in-depth inspection must be governed by the type and intensity of use.
- Each harness comes with a booklet that must be completed to maintain a record of the harnesses applications.

Before use please check for;

- The Fabric: Cuts, tears, abrasion and damage caused by use, heat, chemicals, etc.
- The Stitching: Cut, torn, worn or loose threads.
- The Buckles: Proper functioning of the buckles.

For more information contact :

T: +44 (0) 1902 451 451 F: +44 (0) 1902 451 276 E: sales@ultimateindustrial.co.uk www.ultimateindustrial.co.uk Ultimate Industrial Limited Victoria House, Colliery Road, Wolverhampton, WV1 2RD United Kingdom

