COVERALL

FUNCTIONAL AND EFFECTIVE

Versatile PVC goggles that fit over prescription glasses, available in ventilated or sealed versions.





COVERSI (Sealed)









COVARSI (Ventilated)

- **+** ADJUSTABLE STRAP
- **+** FITS OVER PRESCRIPTION GLASSES
- + 2 VERSIONS:

VENTILATED (COVARSI) OR SEALED (COVERSI)



GOVERA

FUNCTIONAL AND EFFECTIVE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
COVERALL	Ventilated	COVARSI	2C-1,2 😭1 BT €€	≅ EN166 3 4 BT C€	ASAF
	Sealed	COVERSI	2C-1,2 🖆1 BT KN €€		Anti-scratch/Anti-fog ()

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

- K. Resistance to surface damage by fine particles
- N. Resistance to fogging
- € European standard Manufacturer name

TECHNOLOGY

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

PACKAGING AND EAN 13 CODE				
	COVARSI	COVERSI		
Individual plastic bag	3660740000820	3660740000837		
5 safety goggles per box	3660740100827	3660740100834		
90 safety goggles per outer pack	3660740200824	3660740200831		

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- 4. Large dust particles > 5 microns.
- **5.** Gas and fine dust particles < 5 microns.
- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- $\textbf{T.}\ \ \text{The letter T, immediately after the mechanical strength symbol, authorises}$ use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 4			
FRAME	PVC			
TEMPLES	Non applicable			
STRAP	Nylon			
FOAM	No			
SPARE LENSES	No			











10/01/2019

Europe Bollé Safety 34 rue de la soie 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.com

