

HPV/A5

Premium Helmet with Wheel Ratchet

Product Datasheet

OUR REF: HPV/A5/WR/(WH, BL, RED)

PRODUCT DESCRIPTION

Stylish, premium ABS helmet available in three popular colours. Comes with a 6 point terylene comfort harness and padded terylene sweatband for maximum user comfort. Easy adjustment wheel ratchet and free chin strap allows for a secure, perfect fit and optimum protection. Ventilation at the top of the helmet allows for added climate control. A sizeable front for logo customisation.

AVAILABLE SIZES: ONE SIZE
(designed to fit 'regular size range')
(52-63cm)

PACKAGING: Individual polybag
Per Case : 20 (Pre-Assembled)

COLOURS AVAILABLE:
Ultimate Blue, Deep Red
and Matt White



Technical Details

These products are classed as Personal Protective Equipment (PPE) under the EU Directive 89/686/EEC **EN 397:2012+A1:2012** "Specification for industrial safety helmets" And **EN50365:2002** "Insulating helmets for use on low voltage installations"

EC type examination(s) carried out by: INSPEC International Ltd. 56 Leslie Hough Way, Salford, GT Manchester M6 6AJ, UK. Notified Body: 0194

Instructions for use:

- Turn ratchet counterclockwise until headband open to largest size, Place helmet on your head. Turn ratchet clockwise until headband is comfortable and secure. **DO NOT OVER TIGHTEN.**
- This electrically insulating helmet cannot be used alone and that it is necessary to use other insulating protective equipment according to the risks involved in the work.
- If the helmet has any impact, scratches, fading or damage, please immediately replace the whole unit.
- During normal use service life is three years.

Additional Information:

- **Cleaning:** Clean with mild detergent. Do NOT use paints, solvents, chemicals, adhesives, petrol or similar substances on this helmet
- **Disinfection:** The parts of this product in contact with the skin should be disinfected periodically (at least every 3months) with a suitable disinfectant solution.
- **Storage:** Always store in clean, dry conditions and contain within the poly bag/box provided. Do not store in places subject to direct, strong sunlight or in contact with solvents.
- **Damage:** This product should be carefully inspected before use and discarded if damaged in anyway whatsoever.
- **Chemicals:** Certain chemicals may have a detrimental effect on contact with this product. If in doubt please check with your supplier.
- **Material Declaration:** No parts of the helmet which are in contact with the wearer are made from materials known to cause skin irritation.

MEETS:
EN 397:2012+A1:2012

SPECIFICATION FOR INDUSTRIAL SAFETY HELMETS



EN 50365
Class 0

This helmet has been tested to very low temperatures of up to **-30°C** and tested for **Lateral Deformation.**

For more information contact:

T: +44 (0) 1902 451 451 **F:** +44 (0) 1902 451 276
E: sales@ultimateindustrial.co.uk
www.ultimateindustrial.co.uk

Ultimate Industrial Limited

Victoria House,
Colliery Road,
Wolverhampton, WV1 2RD
United Kingdom

