Product leaflet

ProductModel No.Ordering No.Protective hoodSR 345H09-1012Protective hoodSR 346H09-1112

Product Description

The protective hoods are designed for use together with Sundström half masks and full face masks with filters or SR 307 compressed air attachment, and with the SR 90 Airline. The hood is made of chemicals-resistant materials and provides protection against splashing and dripping of most solvents and acids in relatively low concentrations. However, the material may be affected by extended contact with certain solvents in liquid form. The hood is extra roomy, so that both a safety helmet and ear protectors can be worn under the hood, if necessary. The SR 345 hood extends over the user's shoulders, back and chest. The SR 346 hood is extended so that it covers the top part of the user's body. The visor is treated to prevent misting.


The hood can be machine-washed about 10 times – without spin-drying – at a maximum of +40 °C.

Technical specification

SR 345, SR 346

Weight SR 345	≈ 200 g	
Weight SR 346	≈ 410 g	
Service temperature	-10 – +55 °C, < 90 % RH	
Storage temperature	-20 – +40 °C, < 90 % RH	
Resistance to chemicals	Requisition list from Sundström Safety AB	
Approval	CE Category 1	

- A. Hood
- **B** Visor
- C. Half mask
- D. Filter combination
- E. Exhalation valve (two)





Head Office

Tel: +46 10 484 87 00

Visiting address: Stockholmsvägen 33 SE-181 33 Lidingö Factory

Tel: +46 10 484 87 00

Visiting address: Västergatan 4 SE-341 50 Lagan

